

**LEAD
THE
FIELD.**

Top-Drive Field GrainBelts



A Soft Touch in a Tough Business.

Brandt's 15LP Top-Drive Field GrainBelts give you the edge you need, delivering high-volume performance with a powerful combination of speed, gentleness, and versatility. Engineered to get the job done quickly and carefully, Brandt conveyors protect your seed investment and maintain grain quality, all while moving up to 6,500 bu/hr.

① Performance Boost

Get better performance with gentle handling:

- The optimized intake and transition increases grain-flow efficiency to achieve peak performance in varying conditions.
- Capacity is optimized to match bin unload systems up to 6,500 bu/hr on a 10hp electric motor, increasing efficiency.
- The optional wrap roller increases the contact area of the belt on the drive roller for more consistent traction and performance.

② Maximum Versatility

Achieve ultimate product retention with these versatile machines:

- The double lip intake seal keeps your crop on the belt where it belongs, increasing product retention while loading.
- Lowest clearance intake hoppers (8") with retractable hopper fabric that extends up 16" for accessing lower bin unload systems.
- Belt wipers in the intake and discharge keep the return side of the belt free from debris and build-up, reducing uneven wear and tear on the belt and drive components.

③ Easy To Operate

The user-friendly design reduces maintenance costs while promoting operator safety:

- Brandt's EZTRAK tensioning and tracking system keeps your belt aligned and properly tensioned at all times. And, the visual tension indicator makes it easy to see when adjustment is needed.
- The enclosed wind guard delivers environmental protection and operator safety.
- The pre-wired switchbox and plug electric drives allow for setup-free operation.

Powerful Value. **Delivered.**

Brandt

TOP-DRIVE FIELD GRAINBELTS

SPECIFICATIONS

	1535TD	1545TD
Performance		
Capacity (bushels per hour)	6,500	6,500
Recommended Horsepower - Electric	7.5 - 10	7.5 - 10
Dimensions		
Belt Width	15"	15"
Conveyor Length	37'	47'
Raised Height	17' 5"	23'
Raised Reach	13' 5" Electric / 15' Hydraulic	16' 9" Electric / 18' 11" Hydraulic
Lowered Reach	15' Electric / 17' 3" Hydraulic	20' 3" Electric / 23' 1" Hydraulic
Transport Height (hitch at 12")	10' 7"	11' 8"
Transport Length	40' 5"	48' 1"
Intake Reach	11' 11" Electric / 9' 6" Hydraulic	12' Electric / 9' 1" Hydraulic
Wheel Track Width	94"	94"
Total Weight	1,720 lb	2,030 lb
Tube Diameter	10"	10"
Tire Size	ST205/75D15	ST205/75D15
Features		
Lift Mechanism	Manual Winch	Manual Winch
Windguards	Standard	Standard
Drive System	Top-Drive	Top-Drive
Hopper		
Hopper Style	Low Profile	Low Profile
Hopper Width and Length	36" x 60"	36" x 60"
Collapsed Hopper Height	8"	8"
Extended Hopper Height	16"	16"

OPTIONS

Weight transfer kit

to prevent upending the conveyor

Electric or hydraulic drive option

to suit your operational needs

For more information
Call us at 1-866-4-BRANDT
Email us at agriculture@brandt.ca
Or visit us at www.brandt.ca

Brandt Agricultural Products
PO Box 317, 13th Avenue & Pinkie Road
Regina, SK, Canada
S4P 3A1

